

GW - RG6 /U - CU Standard Cable

Product Code: 213GWRG6/U1C

Product Code: 213GWRG6/U3C

Condruction Parameters:



- Conductor: 18 AWG Solid Bare Copper
- Dielectric: 4.80mm Foam Polyethylene
- Shielding 1 : Bonded AL Foil
- Shielding 2 : 40% AL-Mg alloy wire(16*4*0.12mm)
- Cable Dimensions Jacket: 6.8mm PVC (CM Rate)



Electrical Properties:

Nominal Impedance(Ω)	75
Nominal Velocity of Propagation(%)	85
Nominal Capacitance (Pf/m)	50
Speaker Test(VAC)	4000

SRL(Db)	Frequency(MHz)	Maximum (Db/100ft)	Maximum(Db/100m)
Attenuation [@68o F. (20o C.)]	5	0.58	1.9
	55	1.6	5.25
	187	2.85	9.35
	300	3.55	11.64
	450	4.4	14.43
	600	5.1	16.73
	750	5.65	18.54
	865	6.1	20.01
	1000	6.55	21.49

Package

1) Reel in box.



2) Wooden spool



General Wires

P.O. BOX: 663, Buffalo, NY 142400663

TEL: 1 718 766 8635

www.generalwire.us



MADE IN USA